



ECO FORM FILM FACED PLYWOOD

SKU: FFP0100

Eco Form is a most effective cost-saving 2-time hotpress Film Faced Plywood on the market. Equipped with 100% Hardwood, this product will outperform any 1-time hotpress poplar plywood in the market.

ADDITIONAL INFORMATION

Sizes	Dimensions (mm)	1250×2500 mm 910×1820 mm 1220×2440 mm	
	Thickness (mm)	11 11.5 12 15 18 21 9	
Materials	Face	High-gsm 165 gsm Standard	
	Back	High-gsm 165 gsm Standard	
	Color	Dark Brown	
	Wood Species	Eucalyptus Acacia	
	Core Grade	Mixed Grade	
	Glue Type	WBP Melamine Economy	
Application	Application	Formwork	
	Formaldehyde Emissions	E2	
	Maximum Repetition (times)	6	

Listed product attributes are for reference only.
Contact us for product customization and best price offer today!



Technical Performance

Width & Length Tolerances (mm)	1.0 per meter
Thickness Tolerance (mm)	EN315
Moisture Content (%)	12
Density (kg/m ³)	550
Bonding Strength (Mpa)	1.0
Mean Modulus of Elasticity (Along Grain) (Mpa)	5000
Mean Modulus of Elasticity (Across Grain) (Mpa)	4000
Min Bending Strength (Along Grain) (Mpa)	50
Min Bending Strength (Across Grain) (Mpa)	40
Thickness Swelling (%)	8

Listed product attributes are for reference only.
Contact us for product customization and best price offer today!