



4 FT X 8 FT - ECO FORM PLUS - FILM FACED PLYWOOD

SKU: FFP01PL

Eco Form Plus is an upgrade from our most economical product line — Eco Form. Eco Form can be used for approximately 6-8 times which are best for market that requires strict quality while having to maintain most competitive pricing. Eco Form Plus is a sweet spot Vietnam Film faced Plywood product from Vinawood – a renowned Vietnam Plywood Supplier.

WHY ECO FORM PLUS VIETNAM FILM FACED PLYWOOD?

Looking for a quality plywood that doesn't break the bank? Look no further than Vinawood's Eco Form Plus Film Faced Plywood. This product is perfect for markets that require a price-sensitive Vietnam plywood product while maintaining consistent quality and offering some premium features.

WHAT IS FILM FACED PLYWOOD?

Film Faced Plywood is made from plywood that is strengthened with cross-wise structure. Film Faced Plywood is often used for formwork and shuttering purposes. Coated with 100% phenolic film, Film Faced Plywood will withstand many repetitions of concrete pouring while sustaining smooth concrete quality.

WHAT IS IMPORTANT IN CHOOSING FILM FACED PLYWOOD?

Key decision factors of Film Faced Plywood are its species, film coating, and repetition. These factors will determine how durable the panels will be, and the concrete surface they produce.

WHY VINAWOOD?

VINAWOOD is a mill in Vietnam with well-known reputation of over 30 years. VINAWOOD is also familiar with many standards and timber regulations that will make your journey consuming these panels easier. Over the past year, VINAWOOD maintains 99% satisfaction rates. It is also familiar with multi-modal shipping that will deliver Vietnam plywood to you fast, cheap, and safe. VINAWOOD is plywood supplier of Top 5 Formwork companies in the world.

ADDITIONAL INFORMATION

Listed product attributes are for reference only.
Contact us for product customization and best price offer today!



| | | | |
|------------------------------|---|--|--|
| Sizes | Dimensions (mm) | 2440.00 x 1220.00 mm 2500.00 x 1250.00 mm 8 ft x 4 ft | |
| | Thickness (mm) | 1/2" 12.00 13/16" 15.00 18.00 21.00 3/4" 5/8" | |
| Materials | Face | Phenolic Surface Film – High-gsm Standard 165 gsm | |
| | Back | Phenolic Surface Film – High-gsm Standard 165 gsm | |
| | Face Color | Dark Brown | |
| | Back color | Dark Brown | |
| | Wood Species | Acacia,Eucalyptus | |
| | Core Grade | Mixed Grade | |
| | Glue Type | WBP Melamine Standard | |
| Application | Application | Formwork | |
| | Formaldehyde Emissions | E2 | |
| | Maximum Repetition (times) | 8 | |
| Technical Performance | Width & Length Tolerances (mm) | 1mm per 1 meter | |
| | Thickness Tolerance (mm) | According to EN315: +0.56 / -0.76 According to EN315: +0.65 / -0.85 According to EN315: +0.74 / -0.94 According to EN315: +0.83 / -1.03 | |
| | Moisture Content (%) | 12 | |
| | Density (kg/m3) | 570 | |
| | Bonding Strength (Mpa) | 1 | |
| | Mean Modulus of Elasticity (Along Grain) (Mpa) | 4000 5000 7000 8000 | |
| | Mean Modulus of Elasticity (Across Grain) (Mpa) | 4000 5000 6000 3000 | |
| | Min Bending Strength (Along Grain) (Mpa) | 30 35 45 55 | |
| | Min Bending Strength (Across Grain) (Mpa) | 15 20 25 30 | |
| | Thickness Swelling (%) | 8 | |
| More | Brand Name | VINAWOOD | |
| | Model Number | FFP01PL2440122012 FFP01PL2440122015 FFP01PL2440122018 FFP01PL2440122021 FFP01PL2500125012 FFP01PL2500125015 FFP01PL2500125018 FFP01PL2500125021 | |
| | Place of Origin | Vietnam | |

Listed product attributes are for reference only.
Contact us for product customization and best price offer today!