

VINAWOOD CO., LTD Sales Office: +84-83-333-2333 Email: plywood@vinawoodltd.com





4 FT X 8 FT - FORM BASIC - FILM FACED PLYWOOD

SKU: FFP0300

Form Basic is our best selling Vietnam Film Faced plywood. It is made from 100% Hardwood, WBP Glue, and Premium Phenolic Coating Surface. This plywood sheet is made and tested with rigorous procedures to ensure quality consistency.

WHY FORM BASIC?

Form Basic has simply the best combination of factors. Its construction made it quite affordable while maintaining the popular number of repetitions needed. Form Basic is our best selling Vietnam Film Faced plywood. It is made from 100% Hardwood, WBP Glue, and Premium Phenolic Coating Surface. This plywood sheet is made and tested with rigorous procedures to ensure quality consistency.

WHAT IS FILM FACED PLYWOOD?

Film Faced Plywood is made from plywood that is strengthened with cross-wise structure. Film Faced Plywood is often used for formwork and shuttering purposes. Coated with 100% phenolic film, Film Faced Plywood will withstand many repetitions of concrete pouring while sustaining smooth concrete quality.

WHAT IS IMPORTANT IN CHOOSING FILM FACED PLYWOOD?

Key decision factors of Film Faced Plywood are its species, film coating, and repetition. These factors will determine how durable the panels will be, and the concrete surface they produce. While phenolic bond panel is clearly a more superior choice, Form Basic is still a best seller with melamine glue. It overperforms in many countries and is a strong candidate for a phenolic bond panel alternative. Why getting a more expensive products if you only expect certain number of usage?

WHY VINAWOOD?

VINAWOOD is a mill in Vietnam with well-known reputation of over 30 years. VINAWOOD is also familiar with many standards and timber regulations that will make your journey consuming these panels easier. Over the past year, VINAWOOD maintains 99% satisfaction rates. It is also familiar with multi-modal shipping that will deliver Vietnam plywood to you fast, cheap, and safe. VINAWOOD is supplier of Top 5 Formwork companies in the world.

Listed product attributes are for reference only. Contact us for product customization and best price offer today!





VINAWOOD CO., LTD Sales Office: +84-83-333-2333 Email: plywood@vinawoodltd.com



ADDITIONAL INFORMATION

Dimensions (mm) 2440.00 x 1220.00 mm | 2500.00 x 1250.00 mm | 8 ft x 4 ft

Sizes Thickness (mm) 1/2" | 12.00 | 13/16" | 15.00 | 18.00 | 21.00 | 3/4" | 5/8"

Alternative Dimensions 4.00×8.00×11/16 | 4.00×8.00×19/32 | 4ft x 8ft x 0.47in | 4ft x 8ft x 0.825in

Face Phenolic Surface Film – High-gsm Standard 165 gsm

Back Phenolic Surface Film – High-gsm Standard 165 gsm

Face Color Dark Brown

Materials Back color Dark Brown

Wood Species Acacia, Eucalyptus

Core Grade AA Grade

Glue Type WBP Melamine Standard

Application Formwork

ApplicationFormaldehyde EmissionsE2

Maximum Repetition (times) 10

Width & Length Tolerances (mm) 1mm per 1 meter

Thickness Tolerance (mm)

According to EN315: +0.56 / -0.76 | According to EN315: +0.65 / -0.85 |

According to EN315: +0.74 / 0.04 | According to EN315: +0.83 / 1.03

According to EN315: +0.74 / -0.94 | According to EN315: +0.83 / -1.03

Moisture Content (%) 12
Density (kg/m3) 600

Technical Bonding Strength (Mpa) 1
Performance

Mean Modulus of Elasticity (Along Grain) (Mpa) 4000 | 6000 | 7000 | 8000 Mean Modulus of Elasticity (Across Grain) (Mpa) 4000 | 5000 | 6000 | 3000

Min Bending Strength (Along Grain) (Mpa) 40 | 50 | 30 | 55

Min Bending Strength (Across Grain) (Mpa) 20 | 25 | 30 | 35

Thickness Swelling (%) 8

Brand Name VINAWOOD

More Model Number FFP03002440122012 | FFP03002440122015 | FFP03002440122018 | FFP03002440122021 |

FFP03002500125012 | FFP03002500125015 | FFP03002500125018 | FFP03002500125021

Place of Origin Vietnam

Listed product attributes are for reference only. Contact us for product customization and best price offer today!

