



4 FT X 8 FT - PRO FORM - FILM FACED PLYWOOD

SKU: FFP0500

Vinawood Pro Form Film Faced Plywood is preferred by Top 5 Formwork companies in the world. Made with high quality hardwood and phenolic glue, Pro Form Eco is very durable and complies to market requirements in Europe and North America.

WHY PRO FORM?

Pro Form is a more affordable option of Pro Form. Vinawood Pro Form Film Faced Plywood is preferred by Top 5 Formwork companies in the world. Made with high quality hardwood and phenolic glue, Pro Form is very durable and complies to market requirements in Europe and North America.

WHAT IS FILM FACED PLYWOOD?

Film Faced Plywood is made from plywood that is strengthened with cross-wise structure. Film Faced Plywood is often used for formwork and shuttering purposes. Coated with 100% phenolic film, Film Faced Plywood will withstand many repetitions of concrete pouring while sustaining smooth concrete quality.

WHAT IS IMPORTANT IN CHOOSING FILM FACED PLYWOOD?

Key decision factors of Film Faced Plywood are its species, film coating, and repetition. These factors will determine how durable the panels will be, and the concrete surface they produce.

Pro Form is the highlight of Vietnam Film Faced Plywood due to its compliance with majority of international standards while being very reasonable priced.

WHY VINAWOOD?

VINAWOOD is a mill in Vietnam with well-known reputation of over 30 years. VINAWOOD is also familiar with many standards and timber regulations that will make your journey consuming these panels easier. Over the past year, VINAWOOD maintains 99% satisfaction rates. It is also familiar with multi-modal shipping that will deliver Vietnam plywood to you fast, cheap, and safe. VINAWOOD is supplier of Top 5 Formwork companies in the world.

Listed product attributes are for reference only.
Contact us for product customization and best price offer today!



ADDITIONAL INFORMATION

Sizes	Dimensions (mm)	2440.00 x 1220.00 mm 2500.00 x 1250.00 mm 8 ft x 4 ft	
	Thickness (mm)	1/2" 12.00 13/16" 15.00 18.00 21.00 3/4" 5/8"	
	Alternative Dimensions	4.00×8.00×11/16 4.00×8.00×19/32 4ft x 8ft x 0.47in 4ft x 8ft x 0.825in	
Materials	Face	Phenolic Surface Film – Top grade 125 gsm	
	Back	Phenolic Surface Film – Top grade 125 gsm	
	Face Color	Dark Brown	
	Back color	Dark Brown	
	Wood Species	Acacia,Eucalyptus	
	Core Grade	AA Grade	
	Glue Type	WBP Phenolic	
Application	Application	Formwork	
	Formaldehyde Emissions	E1	
	Maximum Repetition (times)	20	
Technical Performance	Width & Length Tolerances (mm)	1mm per 1 meter	
	Thickness Tolerance (mm)	According to EN315: +0.56 / -0.76 According to EN315: +0.65 / -0.85 According to EN315: +0.74 / -0.94 According to EN315: +0.83 / -1.03	
	Moisture Content (%)	12	
	Density (kg/m3)	600	
	Bonding Strength (Mpa)	1	
	Mean Modulus of Elasticity (Along Grain) (Mpa)	4000 6000 7000 8000	
	Mean Modulus of Elasticity (Across Grain) (Mpa)	4000 5000 6000 3000	
	Min Bending Strength (Along Grain) (Mpa)	40 50 30 55	
	Min Bending Strength (Across Grain) (Mpa)	20 25 30 35	
	Thickness Swelling (%)	8	
More	Brand Name	VINAWOOD	
	Model Number	FFP05002440122012 FFP05002440122015 FFP05002440122018 FFP05002440122021 FFP05002500125012 FFP05002500125015 FFP05002500125018 FFP05002500125021	
	Place of Origin	Vietnam	

Listed product attributes are for reference only.
Contact us for product customization and best price offer today!