

VINAWOOD CO., LTD Sales Office: +84-83-333-2333 Email: plywood@vinawoodltd.com





4 FT X 8 FT - PRO FORM - FILM FACED PLYWOOD

SKU: FFP0500

Vinawood Pro Form Film Faced Plywood is preferred by Top 5 Formwork companies in the world. Made with high quality hardwood and phenolic glue, Pro Form Eco is very durable and complies to market requirements in Europe and North America.

WHY PRO FORM?

Pro Form is a more affordable option of Pro Form. Vinawood Pro Form Film Faced Plywood is preferred by Top 5 Formwork companies in the world. Made with high quality hardwood and phenolic glue, Pro Form is very durable and complies to market requirements in Europe and North America.

WHAT IS FILM FACED PLYWOOD?

Film Faced Plywood is made from plywood that is strengthened with cross-wise structure. Film Faced Plywood is often used for formwork and shuttering purposes. Coated with 100% phenolic film, Film Faced Plywood will withstand many repetitions of concrete pouring while sustaining smooth concrete quality.

WHAT IS IMPORTANT IN CHOOSING FILM FACED PLYWOOD?

Key decision factors of Film Faced Plywood are its species, film coating, and repetition. These factors will determine how durable the panels will be, and the concrete surface they produce.

Pro Form is the highlight of Vietnam Film Faced Plywood due to its compliance with majority of international standards while being very reasonable priced.

WHY VINAWOOD?

VINAWOOD is a mill in Vietnam with well-known reputation of over 30 years. VINAWOOD is also familiar with many standards and timber regulations that will make your journey consuming these panels easier. Over the past year, VINAWOOD maintains 99% satisfaction rates. It is also familiar with multi-modal shipping that will deliver Vietnam plywood to you fast, cheap, and safe. VINAWOOD is supplier of Top 5 Formwork companies in the world.

Listed product attributes are for reference only. Contact us for product customization and best price offer today!





VINAWOOD CO., LTD Sales Office: +84-83-333-2333 Email: plywood@vinawoodltd.com



ADDITIONAL INFORMATION

Dimensions (mm) 2440.00 x 1220.00 mm | 2500.00 x 1250.00 mm | 8 ft x 4 ft **Sizes** Thickness (mm) 1/2" | 12.00 | 13/16" | 15.00 | 18.00 | 21.00 | 3/4" | 5/8"

> Alternative Dimensions 4.00×8.00×11/16 | 4.00×8.00×19/32 | 4ft x 8ft x 0.47in | 4ft x 8ft x 0.825in

Face Phenolic Surface Film - Top grade 125 gsm Phenolic Surface Film - Top grade 125 gsm Back

Face Color Dark Brown **Materials** Back color Dark Brown

> **Wood Species** Acacia, Eucalyptus

Core Grade AA Grade **WBP** Phenolic Glue Type

Application Formwork

Application F1 Formaldehyde Emissions Maximum Repetition (times) 20

Width & Length Tolerances (mm) 1mm per 1 meter

According to EN315: +0.56 / -0.76 | According to EN315: +0.65 / -0.85 | Thickness Tolerance (mm)

According to EN315: +0.74 / -0.94 | According to EN315: +0.83 / -1.03

Moisture Content (%) 12 600 Density (kg/m3) Bonding Strength (Mpa)

Performance Mean Modulus of Elasticity (Along Grain) (Mpa) 4000 | 6000 | 7000 | 8000

Mean Modulus of Elasticity (Across Grain) (Mpa) 4000 | 5000 | 6000 | 3000

Min Bending Strength (Along Grain) (Mpa) 40 | 50 | 30 | 55 Min Bending Strength (Across Grain) (Mpa) 20 | 25 | 30 | 35

Thickness Swelling (%) 8

Brand Name VINAWOOD

FFP05002440122012 | FFP05002440122015 | FFP05002440122018 | FFP05002440122021 | More Model Number

FFP05002500125012 | FFP05002500125015 | FFP05002500125018 | FFP05002500125021

Place of Origin Vietnam

Listed product attributes are for reference only. Contact us for product customization and best price offer today!



Technical