



PRO FORM FILM FACED PLYWOOD

SKU: FFP0500

Pro Form Film Faced Plywood is made of high quality tropical hardwood with Phenolic glue for superior strength.

ADDITIONAL INFORMATION

Sizes	Dimensions (mm)	1250×2500 mm 910×1820 mm 1220×2440 mm	
	Thickness (mm)	12 15 18 21	
Materials	Face	125 gsm Dynea/Surfactor/Equivalent	
	Back	125 gsm Dynea/Surfactor/Equivalent	
	Color	Dark Brown	
	Wood Species	Mixed Hardwood	
	Core Grade	AA Grade	
	Glue Type	WBP Phenolic	
Application	Application	Formwork	
	Formaldehyde Emissions	E1	
	Maximum Repetition (times)	20	

Listed product attributes are for reference only.
Contact us for product customization and best price offer today!



Technical Performance

Width & Length Tolerances (mm)	1.0 per meter
Thickness Tolerance (mm)	EN315
Moisture Content (%)	12
Density (kg/m ³)	630
Bonding Strength (Mpa)	1.0
Mean Modulus of Elasticity (Along Grain) (Mpa)	5000
Mean Modulus of Elasticity (Across Grain) (Mpa)	4000
Min Bending Strength (Along Grain) (Mpa)	50
Min Bending Strength (Across Grain) (Mpa)	40
Thickness Swelling (%)	8

Listed product attributes are for reference only.
Contact us for product customization and best price offer today!