



## 8 FT X 4 FT - PRO FORM HIGH DENSITY - FILM FACED PLYWOOD

**SKU:** FFP05HD

Pro Form High Density takes quality to another level. Vinawood Pro Form High Density Film Faced Plywood is preferred by Top 5 Formwork companies in the world. Made with high density hardwood and phenolic glue, Pro Form High Density is very durable and complies to market requirements in Europe and North America.

### WHY PRO FORM HIGH DENSITY?

[Pro Form High Density](#) takes quality to another level. Vinawood Pro Form High Density Film Faced Plywood is preferred by Top 5 Formwork companies in the world. Made with high density hardwood and phenolic glue, Pro Form High Density is very durable and complies to market requirements in Europe and North America.

### WHAT IS FILM FACED PLYWOOD?

[Film Faced Plywood](#) is made from plywood that is strengthened with cross-wise structure. Film Faced Plywood is often used for formwork and shuttering purposes. Coated with 100% phenolic film, Film Faced Plywood will withstand many repetitions of concrete pouring while sustaining smooth concrete quality.

### WHAT IS IMPORTANT IN CHOOSING FILM FACED PLYWOOD?

Key decision factors of Film Faced Plywood are its species, film coating, and repetition. These factors will determine how durable the panels will be, and the concrete surface they produce. Pro Form High Density is the highlight of Vietnam Film Faced Plywood due to its compliance with majority of international standards while being very reasonable priced.

### WHY VINAWOOD?

[VINAWOOD](#) is a mill in Vietnam with well-known reputation of over 30 years. VINAWOOD is also familiar with many standards and timber regulations that will make your journey consuming these panels easier. Over the past year, VINAWOOD maintains 99% satisfaction rates. It is also familiar with multi-modal shipping that will deliver Vietnam plywood to you fast, cheap, and safe. VINAWOOD is supplier of Top 5 Formwork companies in the world.  
> Read more: [Plywood Sizes & Thickness: Essential Dimensions](#)

Listed product attributes are for reference only.  
Contact us for product customization and best price offer today!



## ADDITIONAL INFORMATION

<b>Sizes</b>	Dimensions (mm)	2440.00 x 1220.00 mm   2500.00 x 1250.00 mm   8 ft x 4 ft	
	Thickness (mm)	1/2"   12.00   13/16"   15.00   18.00   21.00   3/4"   5/8"	
	Alternative Dimensions	4ft x 8ft x 0.47in   4ft x 8ft x 0.825in   4ft x 8ft x 11/16in   4ft x 8ft x 19/32in	
<b>Materials</b>	Face	Phenolic Surface Film – Top grade 125 gsm	
	Back	Phenolic Surface Film – Top grade 125 gsm	
	Face Color	Dark Brown	
	Back color	Dark Brown	
	Wood Species	Acacia,Eucalyptus,Hevea	
	Core Grade	AA Grade	
	Glue Type	WBP Phenolic	
<b>Application</b>	Application	Formwork	
	Formaldehyde Emissions	E1	
	Maximum Repetition (times)	20	
<b>Technical Performance</b>	Width & Length Tolerances (mm)	1mm per 1 meter	
	Thickness Tolerance (mm)	According to EN315: +0.56 / -0.76   According to EN315: +0.65 / -0.85   According to EN315: +0.74 / -0.94   According to EN315: +0.83 / -1.03	
	Moisture Content (%)	12	
	Density (kg/m3)	630	
	Bonding Strength (Mpa)	1	
	Mean Modulus of Elasticity (Along Grain) (Mpa)	5000   6000   7000   9000	
	Mean Modulus of Elasticity (Across Grain) (Mpa)	4000   5000   6000   7000	
	Min Bending Strength (Along Grain) (Mpa)	40   50   60   35	
	Min Bending Strength (Across Grain) (Mpa)	20   25   30   35	
	Thickness Swelling (%)	8	
<b>More</b>	Brand Name	VINAWOOD	
	Model Number	FFP05HD2440122012   FFP05HD2440122015   FFP05HD2440122018   FFP05HD2440122021   FFP05HD2500125012   FFP05HD2500125015   FFP05HD2500125018   FFP05HD2500125021	
	Place of Origin	Vietnam	

Listed product attributes are for reference only.  
Contact us for product customization and best price offer today!